

HD ET HDX SERIES

Snowblowers



	N82-270HD	N82-270HDX	N92-300HD	N92-300HDXTR	N100-340HDXTR
RECOMMENDED HORSEPOWER (HP PTO)	40 @ 75	40 @ 75	75 @ 120	75 @ 120	100 @ 160
CUTTING WIDTH (IN/MM)	82" 2083	82" 2083	92" 2337	92" 2337	100" 2540
CUTTING HEIGHT (IN/MM)	38" 965	36" 914	42" 1067	40,5" 1016	44" 1118
IMPELLER RPM	540	540	540	540	540
IMPELLER DIAMETER (IN/MM)	27 1/2" 699	27 1/2" 699	30" 762	30" 762	34" 864
IMPELLER DEPTH	11" 279	11" 279	12" 305	12" 305	14 1/4" 362
NUMBER OF BLADES	4	4	5	5	5
IMPELLER SHAFT DIAMETER (IN/MM)	1 3/16" 40	1 3/16" 40	1 3/4" 44	2" 51	2" 51
BALANCED IMPELLER	Std	Std	Std	Std	Std
DRUM CENTER HEIGHT (IN/MM)	18 3/4" 476	18 3/4" 476	21 1/4" 540	21" 533	21" 533
ROTARY DRUM	-	-	-	Std	Std
CHUTE ROTATION BY HYDRAULIC MOTOR WITH VALVE (GEAR)	Std	Std	Std	Std	Std
HYDRAULIC DEFLECTOR	Std	Std	Std	Std	Std
MANUAL DEFLECTOR	Opt	Opt	Opt.	Opt.	Opt.
CYLINDER FOR CHUTE DEFLECTOR (IN/MM)	2" X 6" 51 X 152	2" X 6" 51 X 152	2" X 6" 51 X 152	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203
SEMI-INDUSTRIAL CHUTE (2 DEFLECTORS)	Std	Std	Std	Std	Std
HYDRAULIC TELESCOPIC CHUTE	-	-	-	-	Opt.
UPPER AUGER DIAMETER	19 1/2" 495	25" 635	23" 584	30" 762	30" 762
BALANCED AUGER	Std	Std	Std	Std	Std
REVERSIBLE CARBON STEEL BLADE	Std	Std	Std	Std	Std
REVERSIBLE HARDOX 450 BLADE	Opt.	Opt.	Opt.	Opt.	Opt.
REVERSIBLE STAINLESS STEEL BLADE	Opt.	Opt.	Opt.	Opt.	Opt.
TIVAR BLADE	Opt.	Opt.	Opt.	Opt.	Opt.
LATERAL BLADE	Opt.	Std	Opt.	Std	Std
ADJUSTABLE CARBON STEEL SKID SHOES	Std	Std	Std	Std	Std
ADJUSTABLE HARDOX 450 SKID SHOES	Opt.	Opt.	Opt.	Opt.	Opt.
ADJUSTABLE STAINLESS STEEL SKID SHOES	Opt.	Opt.	Opt.	Opt.	Opt.
ADJUSTABLE TIVAR SKID SHOES	Opt.	Opt.	Opt.	Opt.	Opt.
HOSES SUPPORT	Std	Std	80	100	Std
REAR SUPPORT	Std	Std	Std	Std	Std
DRIVING CHAIN NUMBER	80	80	80	100	100
NUMBER OF SAFETY BOLTS	2	2	2	3	3
BEARING DUCTILE IRON CASING	Std	Std	Std	Std	Std
SHAFT P.T.O. STANDARD	T60	T60	T80	T80	T80
1 000 TO 540 REDUCER BOX	-	-	Opt.	Opt.	Opt.
ADJUSTABLE HITCH	Std	Std	Std	Std	Std
HITCH CATEGORY (QH = QUICK HITCH)	1, 1QH,2	1, 1QH,2	2, QH	2, QH	2, QH
APPROX. WEIGHT (LB/KG)	1175 / 533	1340 / 608	1790 / 812	2500 / 1134	2969

* The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft.
Prices and Specifications are subject to change without notice.

© Normand Company Ltd. All rights reserved 2023-11-10

HD ET HDX SERIES

Snowblowers



THE HIGH-PERFORMANCE SNOWBLOWER FOR YOUR TOUGHEST JOBS!



Normand Co. Ltd
cienormand.com



340 Tache Street
 Saint-Pascal (QC) Canada G0L 3Y0
 418 492-2712 • 1 888 666-7626
normand@cienormand.com

N82-270HD | N82-270HDX | N92-300HD | N92-300HDXTR | N100-340HDXTR

HD SERIES

With oil bath



N82-270HD

1. 3 pts plates in **HARDOX** 450
2. Drum liner in **HARDOX** 450
3. Gear box embedded in the drum for better weight distribution
4. Frame sides in **HARDOX** 450



Chain in oil bath in **HARDOX** 450



Impeller with grease fitting and integrated puller (Patent pending)
*Standard on all H series models.

N92-300HD

1. Higher cutting height
2. Oil bath in **HARDOX** 450
3. Impeller in **HARDOX** 450
4. Oversized bearings and auger shafts
5. Wider and stronger screw spirals
6. Reinforcement sides and inside reinforcement in **HARDOX** 450



Industrial type eccentric chain tensioner.
Multi-hole shear plate, for longer life



	N82-270HD	N92-300HD
CUTTING WIDTH (IN/MM)	82" 2083	92" 2337
RECOMMENDED HORSEPOWER (HP PTO)	40 @ 75	75 @ 120
OIL BATH	STD	STD



HDX SERIES

With oil bath and double ribbon auger



N82-270HDX

1. Standard anti spatter deflector
2. Double ribbon auger with teeth in **HARDOX** 450
3. Inside reinforcement in **HARDOX** 450



N92-300HDXTR

1. Standard lateral cutting edges
2. Reinforcement sides in **HARDOX** 450
3. Drum liner in **HARDOX** 450
4. 3-points plates **HARDOX** 450

N100-340HDXTR

1. 34" impeller with 14 1/4" depth
2. Oversized bearings
3. Chain #100 in a oil bath in **HARDOX** 450



	N82-270HDX	N92-300HDXTR	N100-340HDXTR
CUTTING WIDTH (IN/MM)	82" 2083	92" 2337	100" 2540
RECOMMENDED HORSEPOWER (HP PTO)	40 @ 75	75 @ 120	100 @ 160
DOUBLE AUGER RIBBON	STD	STD	STD
OIL BATH	STD	STD	STD

